

General Characteristics

- ▶ Our BladeX can be used in dirty or dusty environments.
- ▶ Aluminum Blades, 24"Ø or 30"Ø.
- ▶ Totally Enclosed Motor, 1 phase, 120V, 2-speed, 1/4HP
- ▶ Ball bearing, permanently lubricated,
- ▶ Switch: rotary on floor models, pull chain on yoke mounted model.
- ▶ cord: SJT type-3 conductor 10" long
- ▶ guards: spiral wire front and rear
- ▶ Housing: powder coated 20 gauge Steel



Product Applications

- ▶ Industrial and Commercial use. Cool factories, shops, bakeries, loading docks, laundries, gymnasiums, warehouses, aircraft hangars, and virtually any place a high volume of air movement is required.



Warranty

- ▶ Manufacturer's Warranty: 1 year.

Specific Characteristics

Item #	Ø in.	CFM		Volts	Amp	HP	Drive Type	Motor Enclosure	Blade	Type	Weight lbs	Size in. L,W,H
		High	Low									
USBLX-001	24"	6800	5000	120	2.2	1/4	Direct	Totally Enclosed	Aluminum	Floor	52	26,26,20
USBLX-002	24"	6800	5000	120	2.2	1/4	Direct	Totally Enclosed	Aluminum	Yoke	52	26,26,20
USBLX-003	24"	6800	5000	120	2.2	1/4	Direct	Totally Enclosed	Aluminum	Ceiling	52	26,26,20
USBLX-004	30"	7800	6000	120	2.5	1/4	Direct	Totally Enclosed	Aluminum	Floor	58	32,32,24
USBLX-005	30"	7800	6000	120	2.5	1/4	Direct	Totally Enclosed	Aluminum	Yoke	58	32,32,24
USBLX-006	30"	7800	6000	120	2.5	1/4	Direct	Totally Enclosed	Aluminum	Ceiling	58	32,32,24