

**General Characteristics of Busy Exhaust Paddle Exhaust Wall Fan**

The VentDepot Busy Exhaust is a commercial fan recommended for dependable quiet ventilation. This is a belt driven exhaust fan. The Busy Exhaust motors are totally enclosed or open drip proof. Units are available from 1/3 to 3/4 HP, ranging from 3,900 to 18,200 CFM). Built with an all welded tubular steel frame and finished off with a durable polyester powder coat. With Paddle, deep pitched, rolled venturi blades for maximum air flow. Includes an "Automatic Belt Tensioning System" which extends motor life and eliminates the need for manual belt adjusting. The two speed, single phase motors are available up to 1/2Hp, 115V. All dual voltage, single phase units are prewired at 115v.

**Product Applications of Busy Exhaust Paddle Exhaust Wall Fan**

Recommended for all commercial applications, gymnasiums, factories, warehouses, etc. Utilized for places where dependable quiet ventilation is required.

**Warranty of Busy Exhaust Paddle Exhaust Wall Fan**

Manufacturer's Limited Warranty: 3 Years.



**Specific Characteristics of Busy Exhaust Paddle Exhaust Wall Fan**

Item #	Manufacturer #	Ø Dia. In.	CFM			RPM	Volts V	Amps A	Phase Ph	HP	Drive Type	Motor Enclosure Type	Shipping Weight and Dimensions	
			0.0	0.125	0.25								Lbs	L,W,H In.
<b>USBXX-001</b>	V2412-V	24	3,920	2,070	930	1725	115	6.5	1	1/3	Belt	*ODP	55	32,18,32
<b>USBXX-002</b>	V3012-V	30	6,420	4,980	1,790	1275	115	6.5	1	1/3	Belt	*ODP	57	36,18,36
<b>USBXX-003</b>	V3013-V	30	9,560	7,770	4,850	1725	115	9.5	1	1/2	Belt	*ODP	70	36,18,36
<b>USBXX-004</b>	V3013T-U	30	9,560	7,770	4,850	1725/1425	115/230	7.6/3.8	1	1/2	Belt	Enclosed	70	36,18,36
<b>USBXX-005</b>	V3013-X	30	9,560	7,770	4,850	1765	230/460	0.86/1.72	3	1/2	Belt	*ODP	70	36,18,36
<b>USBXX-006</b>	V3613-V	36	10,900	9,160	4,310	1725	115	9.5	1	1/2	Belt	*ODP	74	42,18,42
<b>USBXX-007</b>	V3613T-U	36	10,900	9,160	4,310	1725/1425	115/230	7.6/3.8	1	1/2	Belt	Enclosed	74	42,18,42

## BusyExhaust Paddle Exhaust Wall Fan

Data Sheet

<b>USBXX-008</b>	V3613-X	36	10,900	9,160	4,310	1765	230/460	0.86/1.72	3	1/2	Belt	*ODP	74	42,18,42
<b>USBXX-009</b>	V3614-U*	36	12,100	10,400	5,000	1750	115	6.80/3.76/3.40	1	3/4	Belt	*ODP	80	42,18,42
<b>USBXX-010</b>	V3614-X	36	12,100	10,400	5,000	1760	230/460	1.15/2.30	3	3/4	Belt	*ODP	80	42,18,42
<b>USBXX-011</b>	V4213-V	42	14,200	11,600	5,470	1725	115	9.5	1	1/2	Belt	*ODP	95	48,18,48
<b>USBXX-012</b>	V4213T-U	42	14,200	11,600	5,470	1725/1425	115/230	7.6/3.8	1	1/2	Belt	Enclosed	95	48,18,48
<b>USBXX-013</b>	V4213-X	42	14,200	11,600	5,470	1765	230/460	0.86/1.72	3	1/2	Belt	*ODP	95	48,18,48

Item #	Manufacturer #	Ø Dia. In.	CFM SP			RPM	Volts V	Amps A	Phase Ph	HP	Drive Type	Motor Enclosure Type	Shipping Weight and Dimensions	
			0.0	0.125	0.25								Lbs	L,W,H In.
<b>USBXX-014</b>	V4214-U*	42	15,900	12,300	5,900	1750	115	6.80/3.76/3.40	1	3/4	Belt	*ODP	102	48,18,48
<b>USBXX-015</b>	V4214-X	42	15,900	12,300	5,900	1760	230/460	1.15/2.30	3	3/4	Belt	*ODP	102	48,18,48
<b>USBXX-016</b>	V4813-V	48	17,100	11,500	3,900	1725	115	9.5	1	1/2	Belt	*ODP	111	55,18,55
<b>USBXX-017</b>	V4813T-U	48	17,100	11,500	3,900	1725/1425	115/230	7.6/3.8	1	1/2	Belt	Enclosed	111	55,18,55
<b>USBXX-018</b>	V4813-X	48	17,100	11,500	3,900	1765	230/460	0.86/1.72	3	1/2	Belt	*ODP	111	55,18,55
<b>USBXX-019</b>	V4814-U*	48	18,100	13,800	6,370	1750	115	6.80/3.76/3.40	1	3/4	Belt	*ODP	111	55,18,55
<b>USBXX-020</b>	V4814-X	48	18,100	13,800	6,370	1760	2/30/460	1.15/2.3	3	3/4	Belt	*ODP	111	55,18,55

\*ODP: Open Drip Proof Motor  
 \*Duel Voltage, Single phase and prewired 115v

Dimensions of Busy Exhaust Paddle Exhaust Wall Fan		
Item#	Ø Blade A	Overall Sq. Size. B
<b>USBXX-001</b>	24	30
<b>USBXX-002</b>	30	34
<b>USBXX-003</b>	30	34
<b>USBXX-004</b>	30	34
<b>USBXX-005</b>	30	34
<b>USBXX-006</b>	36	40
<b>USBXX-007</b>	36	40
<b>USBXX-008</b>	36	40
<b>USBXX-009</b>	36	40
<b>USBXX-010</b>	36	40
<b>USBXX-011</b>	42	46
<b>USBXX-012</b>	42	46
<b>USBXX-013</b>	42	46
<b>USBXX-014</b>	42	46
<b>USBXX-015</b>	42	46
<b>USBXX-016</b>	48	52
<b>USBXX-017</b>	48	52
<b>USBXX-018</b>	48	52
<b>USBXX-019</b>	48	52
<b>USBXX-020</b>	48	52



**Dimension Diagrams of Busy Exhaust Paddle Exhaust Wall Fan**

