

General Characteristics of CBT Series Cabinet Exhaust Fans

The CBT Series are an industrial cabinet fan with shutter, all in one exhaust applications. Includes hinged rear guard for easy electrical hook up after fan installation.

For industrial and commercial use.

This is an industrial Exhaust wall fan.

With 120V, 1 phase or 230/460V, 3 phase, ball bearing permanently lubricated and drip proof motor the CBT Series is UL/U-CL listed Units are available from 1/3 to 1HP, ranging from 3270 to 21500CFM.

Permanently lubricated bearings on blade drive shaft.

Made with Aluminum blade and shutter.

20 Gauge powder coated venturi.

18 Gauge galvanized steel housing.

The CBT Series comes with a 1725 RPM motor, with a motor frame size of 56/Shaft: 5/8"

Ships fully assembled.

UL/U-CL listed and meets OSHA standards.

Made in the U.S.A.



Product Applications of CBT Series Cabinet Exhaust Fans

Recommended for all industrial applications where hot air, odors, smokes, fine particles, lint, vapor, and where stagnant air needs to be removed in high volumes.

Suitable for general industrial use, commercial buildings, warehouses, factories, greenhouses, and mills.

Warranty of CBT Series Cabinet Exhaust Fans

Manufacturer's Limited Warranty: 1 Year.

Specific Characteristics of CBT Series Cabinet Exhaust Fans

Item #	Manufacturing #	Size Ø in.	CFM	Volts V	Amperes A	Phase Ph	HP	Drive Type	Motor Enclosure	Weight and Dimensions with Packaging	
										Lbs.	L,W,H In.
USABX-001	CBT-24B	24	3270	115	5	1	1/3	Belt	Totally Enclosed	100	24,30,30
USABX-002	CBT-24B-3	24	3270	230/460	1.9/0.9	3	1/3	Belt	Totally Enclosed	100	24,30,30
USABX-003	CBT-30B	30	7730	115	6	1	1/3	Belt	Totally Enclosed	120	24,36,36
USABX-004	CBT-30B-3	30	7730	230/460	1.9/0.9	3	1/3	Belt	Totally Enclosed	120	24,36,36



**CBT Series
 Cabinet Exhaust Fans
 With Shutters**
 Data Sheet

USABX-005	CBT-36B	36	8100	115	8	1	1/2	Belt	Totally Enclosed	135	20,42,42
USABX-006	CBT-36B-3	36	8100	230/460	2.3/1.1	3	1/2	Belt	Totally Enclosed	135	20,42,42
USABX-007	CBT-42B	42	12400	115	11	1	3/4	Belt	Totally Enclosed	155	20,20,50
USABX-008	CBT-42B-3	42	12400	230/460	3.3/1.5	3	3/4	Belt	Totally Enclosed	155	20,50,50
USABX-009	CBT-48B	48	13500	115	15	1	1	Belt	Totally Enclosed	200	23,56,56
USABX-010	CBT-48B-3	48	13500	230/460	3.8/1.9	3	1	Belt	Totally Enclosed	200	23,56,56

Dimensions Image of VIK Series ExhaustKit

