



CF-C Series Commercial Air Curtain Data Sheet

General Characteristics of Commercial Air Curtain CF-C Series

The CF-C Series was constructed with a super thing body and full metal housing. UL/U-CL listed.

It is installed with 2 speed cross flow fans and adjustable air deflector.

Includes discharge vanes which extend the entire width of the unit and are adjustable for optimum performance of air flow.

These units are 120v at 60Hz and have a mechanical control.

Motors are heavy duty, PSC and direct drive high efficiency.

Motors permanently lubricated for long life and have thermal over load protection.

Motor has double insulation protection for quieter operation.

Quick disconnects supplied to accommodate easy installation and service of motor.

Units are horizontally stackable to cover longer doorways.

Product Applications of Commercial Air Curtain CF-C Series

Keeps temperature control and odor control of your door passes in your factory, warehouse, supermarket store, and restaurant by providing a high speed air stream curtain.

Suitable for general industrial use, commercial buildings, warehouses, factories, greenhouses, and mills.

Warranty of Commercial Air Curtain CF-C Series

Manufacturer's Limited Warranty: 1 Year.

VentBepet	

Specific Characteristics of Commercial Air Curtain CF-C Series												
Item#	Manufacturing #	Watts W	GFM		FPM		Noise Level (dB)		Weight and Dimensions with Packaging			
	#	vv	HIGH	LOW	HIGH	LOW	HIGH	LOW	Lbs.	١	N,H,L In	
USTNC-001	CF35-C	300	1177	942	2560	1968	67	35	35	10	12	37
USTNC-002	CF47-C	350	1648	1295	2560	1968	67	47	45	10	12	49
USTNC-003	CF59-C	400	2119	1648	2560	1968	69	59	50	10	12	61

Dimensions of Commercial Air Curtain CF-C Series							
Series	Length A	Width B	Height C				
USTNC-001	35	8-3/4	10-1/4				
USTNC-002	47	8-3/4	10-1/4				
USTNC-003	59	8-3/4	10-1/4				







