



General Characteristics of CKTD & KT Industrial Series

The CKTD & KT Series is an industrial line voltage thermostat series.
 For both industrial and commercial environments.
 Is for indoor use only, and used for spot heating areas.
 Series Types: CKTD- Coil Capillary KT- Bi-Metal Models
 Created with SPDT (Single Pole Double Throw) & SPDT (Single Pole Double Throw.)
 Hard wired models rated for 22A resistive @ 125-250 VAC.
 Corded models rated for 13A resistive @ 125 VAC.
 Has a -10 o F to 100 o F Temperature Range.
 Made with a rugged steel Case.
 Is CSA (Canadian Standards Association) Listed
 This item is also UL/U-CL Listed.
 Compliant with RoHS2 Directive (2011/65/EU), that of which includes the application exemptions outlined in Annex III of the directive (KT models only.)



Product Applications of CKTD & KT Industrial Series

For Industrial and commercial environments.
 For indoor use this product is utilized in warehouses, factories, and work areas.
 Ideal for spot heating.

Warranty of CKTD & KT Industrial Series

Manufacturer's Limited Warranty: 1 Year.




Specific Characteristics of CKTD & KT Industrial Series

Item #	Manufacturing #	Description	Amperes A	VAC	Range (°F)	Connection Type	Temp. Scale	Weight and Dimensions with Packaging	
								Lbs.	L,W,H In.
USITK-001	CKTD110	SPDT Heat or Cool	22	125-250	40 - 110	Wire Leads	F	3	4,4,8
USITK-002	KT110	SPST Heat Only	22	125-250	-10 - 100	Wire Leads	C&F	3	4,4,7
USITK-003	KT121	SPST Heat Only	13	125	-10 - 100	6' Cord/Plug	C&F	3	4,4,7
USITK-004	KTD110	SPDT Heat or Cool	22	125-250	-10 - 100	Wire Leads	C&F	3	4,4,7
USITK-005	KTO110	SPST Cool Only	22	125-250	-10 - 100	Wire Leads	C&F	3	4,4,7
USITK-006	KTO121	SPST Cool Only	13	125	-10 - 100	6' Cord/Plug	C&F	3	4,4,7



Dimensions (in) of CKTD & KT Industrial Series

Series	Length A	Width B	Height C
USITK-001	2.63"	2.13"	6.75"
USITK-002 to 006	2.63"	2.13"	5.5"



- Height of the CKTD Series includes Coil.
- Length is from the back of the case to the front of the knob for both CKTD & KT Series.

Short Description of CKTD & KT Industrial Series

Item #	Manufacturing #	Short Description 70 Characters Maximum
USITK-001	CKTD110	SPDT Heat & Cool, 22A, 125-250VAC, Range 40°-110°, Wire Leads, F°.

SEO Table of CKTD & KT Industrial Series

Title
TPI CKTD & KT Industrial Series Thermostats & Controls.
Meta Description
TPI CKTD & KT Industrial Series Thermostats & Controls for Commercial Use, TPI CKTD & KT Industrial Series Thermostats & Controls for Industrial Use, TPI CKTD & KT Industrial Series Thermostats & Controls for Indoor Use, TPI CKTD & KT Industrial Series Thermostats & Controls for Spot Heating Use, TPI CKTD & KT Industrial Series Thermostats & Controls for Heating and Cooling Control Use.
Meta Key Words
TPI CKTD & KT Industrial Series Thermostats & Controls for Commercial Use, TPI CKTD & KT Industrial Series Thermostats & Controls for Industrial Use, TPI CKTD & KT Industrial Series Thermostats & Controls for Indoor Use, TPI CKTD & KT Industrial Series Thermostats & Controls for Spot Heating Use, TPI CKTD & KT Industrial Series Thermostats & Controls for Heating and Cooling Control Use.
Meta URL (file name)
Tpi-cktd-&-kt-industrial-series-thermostats-&-controls-us-english.htm

Product Line Description of CKTD & KT Industrial Series

```

<FONT Size=1>
<b>Product Description:</b> TPI CKTD & KT Industrial Series Thermostats & Controls<br>
<b>Weather Rating:</b> Indoor<br>
<b>Poles & Throw:</b> SPDT & SPST<br>
<b>Heat and/or Cool:</b> Cool Only, Heat Only or Heat & Cool <br>
<b>Amperes:</b> 13 or 22A<br>
<b>VAC:</b> 125-250 or 125<br>
<b>Range (°F):</b> 40-110° of -10-100°<br>
<b>Damper Options:</b> With or without<br>
<b>Connection Type:</b> Wire Leads or 6' Cord/Plug<br>
<b>Temp. Scale:</b> °F or °C&°F<br>
<b>Product Type:</b> TPI CKTD & KT Industrial Series<br>
<b>Usual Delivery Time or Lead Time:</b> 1 to 2 weeks<br>
<b>Shipping Type:</b> Fedex, UPS Package, LTL Freight<br>
</FONT>
    
```