

**General Characteristics of CMPC Heat Buster Direct Drive Ceiling Mount Barrel Fan**

The CMPC Heat Buster is a belt driven top of the line barrel fan.  
 Can be used in industrial or commercial areas.  
 For indoor use.  
 Designed with an attractive heavy-duty tubing steel, wide body barrel.  
 Finished off with a powder coating and a compact easy grip handle.  
 Comes with an automatic belt tensioner.  
 Units are 115, 60hz, single phase. With single or two speed  
 Motors are open drip proof or totally enclosed.  
 Meeting OSHA requirements the CMPC Heat Buster has a 10' grounded, 3 conductor cord with molded plug and spiral wound wire guards.  
 All weights are approximate and may vary slightly.

**Product Applications of CMPC Heat Buster Direct Drive Ceiling Mount Barrel Fan**

It is used to cool factories, shops, bakeries, loading docks, laundries, gymnasiums, warehouses, aircraft hangars, and virtually any place a high volume of air movement is required. The fans portability allows it to be placed in convenient locations and can be easily put away for storage.

**Warranty of CMPC Heat Buster Direct Drive Ceiling Mount Barrel Fan**

Manufacturer's limited warranty in the US: 3 years.  
 Warranty void if fan is left in rain or snow.  
 These products are built to order, therefore they are non-returnable or non-refundable.



**Specific Characteristics of CMPC Heat Buster Direct Drive Ceiling Mount Barrel Fan**

Item #	Manufacturing #	Size Ø (In.)	CFM	Volts V	Amps A	Phases Ph	HP	RPM	Hz	Drive Type	Motor Type	Weight and Dimensions with Packaging	
												Lbs.	L,W,H In.
<b>USDCF-001</b>	CMPC3021	30	8,200/6,600	115	3.8	1	1/4	825/680	60	Direct	Open	98	14,38,39
<b>USDCF-002</b>	CMPC3613	36	10,900	115	6.0	1	1/2	825	60	Direct	Open	182	21,46,53



<b>USDCF-003</b>	CMPC4213	42	13,600	115	6.0	1	½	825	60	Direct	Open	192	21,52,58
<b>USDCF-004</b>	CMPC4815	48	19,100	115	9.1	1	1	850	60	Direct	Open	240	26,59,65

**Dimension (In.) of CMPC Heat Buster Direct Drive Ceiling Mount Barrel Fan**

Series	Length A (In.)	Width B (In.)	Height C (In.)
USDCF-001	12"	36"	37"
USDCF-002	19"	44"	51"
USDCF-003	19"	51"	56"
USDCF-004	24"	57"	63"

