



General Characteristics

The VentDepot CoolChill is a practical, rugged, low-cost air mover used worldwide.

- Built with heavy gauge cold rolled steel barrels.
- 10 Ft. grounded, 3 conductor cord with molded plug.
- Conveniently located guarded on/off switch on wheeled models.
- Tough, rubber tread wheels.
- Spiral wound wire guard meets OSHA requirements.
- Attractive bronze powder coat finish.
- Full width handle.

Product Applications

It is used to cool factories, shops, bakeries, loading docks, laundries, gymnasiums, warehouses, aircraft hangars, and virtually any place a high volume of air movement is required.

The fans portability allows it to be placed in convenient locations and can be easily put away for storage.

Warranty

Manufacturer's Limited Warranty: 3 Years.



Specific Characteristics										
Item #	Ø Blade in.	CFM	RPM	Voltage	А	HP	Drive Type	Motor Enclosure	Weight Ibs	Size in. L,W,H
USFBP-001	36	12100	500	115	7.6	1/2	Belt	Totally Enclosed	132	39,27,41
USFBP-002	42	14445	500	115	7.6	1/2	Belt	Totally Enclosed	142	44,27,45
USFBP-003	42	15850	505	115	13.0	3/4	Belt	Totally Enclosed	148	44,27,45
USFBP-004	42	16990	475	115	11.0	1	Belt	Totally Enclosed	193	44,27,45
USFBP-005	48	19460	475	115	11.0	1	Belt	Totally Enclosed	227	50,28,51
USFBP-006	60	30100	370	115	17.0	1 1/2	Belt	Totally Enclosed	232	64,36,66