VentDepot • §



General Characteristics

The VentDepot CoolRoller is a practical, rugged, low-cost air mover used worldwide.

- Built with heavy gauge cold rolled steel barrels.
- 10 Ft. grounded, 3 conductor cord with molded plug.
- Conveniently located guarded on/off switch on wheeled models.
- Tough, rubber tread wheels.
- Spiral wound wire guard meets OSHA requirements.
- Attractive bronze powder coat finish.
- Motor options: 50 Hertz, explosion proof or totally enclosed.

Frame is heavy duty tubing.

Tilts 90° up or down with positive locktilt control.

Product Applications

It is used to cool factories, shops, bakeries, loading docks, laundries, gymnasiums, warehouses, aircraft hangars, and virtually any place a high volume of air movement is required.

The fans portability allows it to be placed in convenient locations and can be easily put away for storage.

Warranty

Manufacturer's Limited Warranty: 3 Years.



Specific Characteristics											
Item #	Ø in.	CFM	RPM	V	A	Phas e	ΗP	Drive Type	Motor Enclosure	Weight Ibs	Shipping Size in. (W,H,L)
USTBP-001	36	12100	480	115	7.5	1	1⁄2	Belt	Open	156	45,24,49
USTBP-002	36	12100/8060	480/336	115	7.5	1	1⁄2	Belt	Open	156	45,24,49
USTBP-003	42	14445	525	115	7.5	1	1⁄2	Belt	Open	193	52,25.5,54
USTBP-004	42	14445/9950	525/367	115	7.3	1	1⁄2	Belt	Open	193	52,25.5,54
USTBP-005	42	16900	525	115	13.0	1	3⁄4	Belt	Open	193	52,25.5,54
USTBP-006	48	19460	500	115	11.0	1	1	Belt	Totally Enclosed	251	57,26,62