



## **General Characteristics**

The VentDepot ExploTilt is a practical, rugged, low-cost air mover used worldwide.

Fans are equipped with a ONE speed explosion proof motor, aluminum fan blade assembly but WITHOUT switch or wiring.

Motors supplied are Class I, Div. 1, Groups C & D and Class II, Div. 1, Groups F & G.

Built with heavy gauge cold rolled steel barrels.

Spiral wound wire guard meets OSHA requirements.

Attractive bronze powder coat finish.

Frame is heavy duty tubing.

Tilts 90° up and swivels 360°.

Includes safety cable.

## **Product Applications**

It is used to cool factories, shops, bakeries, loading docks, laundries, gymnasiums, warehouses, aircraft hangars, and virtually any place a high volume of air movement is required.

CAUTION, WARNING: Although this product is supplied with an explosion proof motor and aluminum spark arresting fan blade, it is not intended to convey the suitability of the overall finished product in an explosive atmosphere, but only that the product has been supplied with certain components for this purpose. Wiring must be in accordance with local, state and national codes and be performed by a qualified electrician.



## Warranty

Manufacturer's Limited Warranty: 3 Years.

Specific Characteristics											
Item #	Ø in.	CFM	RPM	V	Α	Phase	HP	Drive Type	Motor Enclosure	Weight lbs	Shipping Size in. (W,H,L)
USEHT-001	36	12100	480	115	7.5	1	1/2	Belt	<b>Explosion Proof</b>	209	45.5,22,55
USEHT-002	42	14445	380	115	7.5	1	1/2	Belt	<b>Explosion Proof</b>	241	50.5,22,52.5
USEHT-003	42	15850	525	115	13.0	1	3/4	Belt	<b>Explosion Proof</b>	243	50.5,22,52.5
USEHT-004	48	19460	500	115	11.0	1	1	Belt	<b>Explosion Proof</b>	256	56,22,61.5