

**General Characteristics of Portable Electric Salamander FES-15 & FES-30 Series**

Our FES-15 & FES-30 Series has a Safety yellow heater enclosure with safety screens on both air intake and output openings. The FES-15 & FES-30 Series is the electric alternative to propane and kerosene space heaters. For indoor and outdoor use. ETL-CETL listed. For outdoor use it may require an enclosure as it is not water proof or rain-tight. Optional 25' long cord, ready for plug attachment is available for each model. Cords do not come with plug. Long-life finned tubular heating elements. Thermostat adjustment 40° to 100° F. High-limit thermal cutout switch. CFM Ratings: 800 CFM – 9,10 and 15Kw units, 1100 CFM – 30KW units. Magnetic contactor. Fan only operation feature. 10" wheels. Is the electric alternative to propane and kerosene space heaters. Made in the U.S.A.

**Product Applications of Portable Electric Salamander FES-15 & FES-30 Series**

Recommended for all industrial, commercial, and utility applications where portable high heat output is required. Used frequently in construction, warehouses, loading docks, and workshops.

**Warranty of Portable Electric Salamander FES-15 & FES-30 Series**

Manufacturer's Limited Warranty: 1 Year.



**Specific Characteristics of Portable Electric Salamander FES-15 & FES-30 Series**

Item #	Manufacturing #	CFM	Voltage V	Amperes A	Kilowatts Kw	BTUs	Temp. Rise (°F)	Cord Options	Weight and Dimensions with packaging	
									Lbs.	L,W,H In.



**FES-15 & FES-30 Series**  
**Heat Wave Portable Electric & Wall**  
**Or Ceiling Mounted Salamander**  
Data Sheet

Item #	Manufacturing #	CFM	Voltage V	Amperes A	Kilowatts Kw	BTUs	Temp. Rise (°F)	Cord Options	Weight Lbs.	Dimensions L,W,H In.
<b>USFES-001</b>	FES-1520-3A	800	208	42	15	51195	45	-	67	23,29,41
<b>USFES-002</b>	FES-1520-3A + SO 6/4	800	208	42	15	51195	45	Cord	69	23,29,41
<b>USFES-003</b>	FES-1524-1A	800	240	63	15	51195	45	-	71	25,29,41
<b>USFES-004</b>	FES-1524-1A + SO 4/3	800	240	63	15	51195	45	Cord	73	25,29,41
<b>USFES-005</b>	FES-1524-3E	800	240	36	15	51195	45	-	67	23,29,41
<b>USFES-006</b>	FES-1524-3E + SO 6/4	800	240	36	15	51195	45	Cord	69	23,29,41
<b>USFES-007</b>	FES-1548-3E	800	480	18	15	51195	45	-	67	23,29,41
<b>USFES-008</b>	FES-1548-3E + SO 12/4	800	480	18	15	51195	45	Cord	69	23,29,41
<b>USFES-009</b>	FES-1560-3A	800	600	15	15	51195	90	-	60	23,29,41

Item #	Manufacturing #	CFM	Voltage V	Amperes A	Kilowatts Kw	BTUs	Temp. Rise (°F)	Cord Options	Weight and Dimensions with packaging	
									Lbs.	L,W,H In.
<b>USFES-010</b>	FES-1560-3A + SO 12/4	800	600	15	15	51195	90	Cord	60	23,29,41
<b>USFES-011</b>	FES-3048-3A	1100	480	36	30	102390	90	-	85	25,29,41
<b>USFES-012</b>	FES-3048-3A + SO 6/4	1100	480	36	30	102390	90	Cord	87	25,29,41
<b>USFES-013</b>	FES-3060-3A	1100	600	29	30	102390	45	-	67	25,29,41
<b>USFES-014</b>	FES-3060-3A + SO 6/4	1100	600	29	30	102390	45	Cord	69	25,29,41

**Dimensions (in) of Portable Electric Salamander FES-15 & FES-30 Series**

Series	Length A	Width B	Height C
USFES-001 to 004 & 009 to 020	23	29	41
USFES-005 to 008 & 021 to 028	25	29	41



**Features of Portable Electric Salamander FES-15 & FES-30 Series**

- Plug not included with any of the cords.
- There are three cord types 20A, 45A or the 70A.



Manufacturing #	Amp. Rating
SO 6/4	45A
SO 4/3	70A
SO 12/4	20A

Short Description of Portable Electric Salamander FES-15 & FES-30 Series		
Item #	Manufacturing #	Short Description 70 Characters Maximum
USFES-001	FES-1520-3A	800CFM, 208V, 42A, 3PH, 15Kw, 51195BTU's, 45°F Temp. Rise.

SEO Table of Portable Electric Salamander FES-15 & FES-30 Series	
Title	
Fan Forced Portable TPI Salamander FES-15 & FES-30 Series.	
Meta Description	
Fan Forced Portable TPI Salamander FES-15 & FES-30 Series for Industrial Use, Fan Forced Portable TPI Salamander FES-15 & FES-30 Series for Commercial use, Fan Forced Portable TPI Salamander FES-15 & FES-30 Series for Utility Applications, Fan Forced Portable TPI Salamander FES-15 & FES-30 Series for Indoor Use, Fan Forced Portable TPI Salamander FES-15 & FES-30 Series for Outdoor Use, Fan Forced Portable TPI Salamander FES-15 & FES-30 Series High Heat Output use.	
Meta Key Words	
Fan Forced Portable TPI Salamander FES-15 & FES-30 Series for Industrial Use, Fan Forced Portable TPI Salamander FES-15 & FES-30 Series for Commercial use, Fan Forced Portable TPI Salamander FES-15 & FES-30 Series for Utility Applications, Fan Forced Portable TPI Salamander FES-15 & FES-30 Series for Indoor Use, Fan Forced Portable TPI Salamander FES-15 & FES-30 Series for Outdoor Use, Fan Forced Portable TPI Salamander FES-15 & FES-30 Series High Heat Output use.	
Meta URL (file name)	
portable-electric-tpi-salamander-fes-15-&-fes-30-series-us-english.htm	

Product Line Description of Portable Electric Salamander FES-15 & FES-30 Series
<FONT Size=1> <b>Type:</b> Fan Forced Portable TPI Salamander  <b>Manufacturer:</b> TPI  <b>Model Series:</b> FES  <b>Voltage:</b> 208,240,480 or 600V  <b>Amperes:</b> 15,18,29,36,42 or 63A  <b>Phases:</b> 1 or 3Ph  <b>Kilowatts:</b> 15 or 30Kw  <b>Heat Output:</b> 51195 or 102390BTUs  <b>Temp. Rise:</b> 40° or 90°  <b>Cord Options:</b> With or Without  <b>Air Flow:</b> 800 & 1100CFM  <b>Usual Delivery Time or Lead Time:</b> 1 to 2 weeks  </FONT>