

**General Characteristics of FES-09 & FES-10 Series Portable Electric Salamander**

Our FES-09 & FES-10 Series has a Safety yellow heater enclosure with safety screens on both air intake and output openings.  
 Optional 25' long SO type cord, ready for plug attachment is available for each model.  
 ETL-CETL listed  
 9 & 10Kw, 240V, 1Ph factory pre-wired model with 10Ft. cable & straight blade range plug.  
 For indoor and outdoor use.  
 With outdoor use it may require an enclosure as it is not water proof or rain-tight.  
 Long-life finned tubular heating elements.  
 Thermostat adjustment 40° to 100° F.  
 High-limit thermal cutout switch.  
 CFM Ratings: 800 CFM 9, 10 & 15Kw Units  
 1100 CFM – 30Kw units.  
 Magnetic contactor.  
 Fan only operation feature.  
 10" Wheels.  
 Is the electric alternative to propane and kerosene space heaters.  
 Made in the U.S.A.

**Product Applications of FES-09 & FES-10 Series Portable Electric Salamander**

Recommended for all industrial, commercial, and utility applications where portable high heat output is required. Used frequently in construction, warehouses, loading docks, and workshops.

**Warranty of FES-09 & FES-10 Series Portable Electric Salamander**

Manufacturer's Limited Warranty: 1 Year.



**Specific Characteristics of FES-09 & FES-10 Series Portable Electric Salamander**

Item #	Manufacturing #	CFM	Voltage	Amperes	Phase	Kilowatts	BTUs	Temp.	Weight and Dimensions
--------	-----------------	-----	---------	---------	-------	-----------	------	-------	-----------------------



**FES-09 & FES-10 Series  
 Heat Wave Portable Electric & Wall  
 Or Ceiling Mounted Salamander  
 Data Sheet**

			V	A	Ph	Kw		Rise (°F)	with packaging	
									Lbs.	L,W,H In.
<b>USHTH-001</b>	FES-0924-1C	800	240	38	1	9	30717	25	60	23,29,41
<b>USHTH-002</b>	FES-1024-1CA	800	240	42	1	10	34130	30	60	23,29,41

**Dimensions (in) of FES-09 & FES-10 Series Portable Electric Salamander**

Series	Length A	Width B	Height C
USHTH-001 & 002	23	29	41

