



General Characteristics of FlatDry CD100 and CD100E Dehumidifiers

The VentDepot FlatDry, CD100 and CD100E are easy to transport dehumidifiers designed for heavy duty use.

They have rugged epoxy-coated, steel chassis.

A "floating" compressor for vibration & mobility protection.

An adjustable humidistat to control the level of dryness desired

VentDepot offers the FlatDry CD100 and CD100E with a unique "Reverse Cycle" defrosting system, for effective operation in low ambient temperatures

Standard 115V power requirements for operation in any location.

Both models use a water drain.

CD100E - ADDITIONAL FEATURES

Adjustable Alarm Humidistat and "voltage free" connector.

Power On Indicator.

Hours Run Meter provides accurate run time measuring.

Supplied Complete with wall mounting brackets



Product Applications of FlatDry CD100 and CD100E Dehumidifiers

The Ebac CD100 and CD100E are built for use in: Construction, drying paint, laundry mats, garages, storage facilities, basements, labs, offices, homes, commercial buildings, industrial buildings, print shops, restrooms, museums, libraries, video libraries, medical clinics, archive facilities, electrical power houses, swimming pools, gyms, etc.

Warranty of FlatDry CD100 and CD100E Dehumidifiers

FlatDry CD100 and CD100E by Ebac Dehumidifiers have a 1 year manufacturer's warranty.

Technical Characteristics of FlatDry CD100 and CD100E Dehumidifiers by Ebac Dehumidifiers

Item #	Manufacturer #	Water Removal Capacity per 24 hours			Effective Volume		Volts V	Hertz Hz	Amps A	Phase Ph	Refrigerant	Watts W	Heat BTUs	dbs	Shipping Weight and Dimensions With Packaging	
		ppd Pints	Gallons	Liters	Cubic feet	m ³									Lbs.	L,W,H In.
USFTD-001	CD100	97	12.12	45.9	10594	300	115	60	16	1	R407c	1090	12000	66	165	46,20,23
USFTD-002	CD100E	97	12.12	45.9	10594	300	115	60	16	1	R407c	1090	12000	66	185	46,20,23



Product Applications of FlatDry CD100 and CD100E Dehumidifiers by Ebac Dehumidifiers

Applications	CD100	CD100E	Applications	CD100	CD100E
Model No.	1133560	1027500	Model No.	1133560	1027500
Warehouse	√	√	Agriculture	√	-
Basements	-	√	Kitchens	√	-
Factories	√	√	Pumping Stations	√	√
Sports Halls	√	-	Hotel / Motel	√	-
Storage Areas	√	√	Stadiums	√	√
Laboratories	√	√	Ships / Barges	√	-
Oil Rigs	√	√			

Dimensions of FlatDry CD100 and CD100E Dehumidifiers by Ebac Dehumidifiers

VentDepot Item#	Ebac Model No.	Size A In.	Size B In.	Size C In.
USFTD-001	CD100	20	36	16
USFTD-002	CD100E	20	36	16



Efficiency of FlatDry CD100 and CD100E Dehumidifiers by Ebac Dehumidifiers

Internal Temperature	Degree Celsius °C	Degree Fahrenheit °F	Relative Humidity RH
	16° C	60.8° F.	100% to 60%
	18° C.	64.4° F.	100% to 51%
	20° C.	68° F.	100% to 48%
	22° C.	71.6° F.	100% to 46%
	24° C.	75.2° F.	100% to 44%
	26° C.	78.8° F.	100% to 43%
	28° C.	82.4° F.	100% to 42%
	30° C.	86° F.	100% to 41%
	32° C.	89.6° F.	100% to 41%
	34 °C. and Above	93.2° F. and Above	100% to 40%

Do not use dehumidifier if RH vs. Temperature Falls in the Orange Area





FLATDRY
CD100 and CD100E
Heavy Duty Dehumidifier
Data Sheet