

FlexTube

General Characteristics Flexible Tubing and Fittings FlexTube

The VentDepot Flexible Tubing and Fittings FlexTube tubing is rated for 1500 psi working pressure and is 1/4" I.D. making it useful for systems up to 3 gpm.

The VentDepot Flexible Tubing and Fittings FlexTube fittings are two piece field installable and available with a 1/4" MNPT or 1/4" FNPT swivel.

Product Applications Flexible Tubing and Fittings FlexTube

The VentDepot Flexible Tubing and Fittings FlexTube are used as a high pressure feed line alternative to the 3/8" high pressure nylon tubing. The VentDepot Flexible Tubing and Fittings FlexTube allow the feed line to be cut to length and assembled on site and No crimping tools are required.

Warranty of Flexible Tubing and Fittings FlexTube

Manufacturer's Limited Warranty: 5 Years.



Specific Characteristics of Flexible Tubing and Fittings FlexTube												
VentDepot Item #	VentDepot Manufacturing #	Description	Material Type	Shipping Weight		Shipping Size L,W,H						
				lbs	kg	in	cm					
USFXT-001	94001	1/4" Synflex tubing Synflex Feed Line Tubing hose per ft.	Nylon	1	0.453.	12	30.5					
USFXT -002	93512	1/4"Hose Crimp x 1/4" MNPT	Brass	.16	0.072	1,1,.5	2.5,2.5,1.3					
USFXT -003	80450	1/4"Hose Crimp x 1/4" Female Swivel NPT	Brass	.16	0.072	1,1,5	2.5,2.5,1.3					

Image Gallery Flexible Tubing and Fittings FlexTube







1/4" I.D. Synflex Tubing per ft. USFXT-001/94001

1/4"Hose Crimp x 1/4" MNPT USFXT-002/94144

1/4"Hose Crimp x 1/4" Female Swivel NPT USFXT-003/94145



FlexTube

Short Description of Flexible Tubing and Fittings FlexTube								
VentDepot Item #	VentDepot Manufacturing	Short Description 70 Characters Maximum						
	#	123456789012345678901234567890123456789012345678901234567890						
USFXT -001	94001	1/4" Synflex tubing Synflex Feed Line Tubing, rated for 1500 psi working pressure and has a 1/4" I.D						
USFXT -002	94144	1/4"Hose Crimp x 1/4" MNPT, produces a 1500 psi for any mist system up to 3 GPM						
USFXT -003	94145	1/4"Hose Crimp x 1/4" Female Swivel NPT, produces a 1500 psi for any mist system up to 3 GPM.						

SEO Table of Flexible Tubing and Fittings FlexTube							
				Title			
'lexible	Tubing	and	Fittings	FlexTube			
			·	Meta Description			

Flexible Tubing and Fittings FlexTube, Flexible Tubing and Fittings FlexTube for High Pressure Misting
Systems, Flexible Tubing and Fittings FlexTube for Industrial Use, Flexible Tubing and Fittings FlexTube for
Green Houses, Flexible Tubing and Fittings FlexTube for Commercial Use.

Meta Key Words

Flexible Tubing and Fittings FlexTube, Flexible Tubing and Fittings FlexTube for High Pressure Misting Systems, Flexible Tubing and Fittings FlexTube for Industrial Use, Flexible Tubing and Fittings FlexTube for Green Houses, Flexible Tubing and Fittings FlexTube for Commercial Use.

Meta URL (file name)

flexible-tubing-and-fittings-flextube-us-english.htm

Product Line Description of Flexible Tubing and Fittings FlexTube

b>Product Description: Synflex Feed Line Tubing
br>

Use: Misting Systems

Weather Rating: Indoor & Outdoor

Gallons per Minute GPM: 3.0

Spray Degrees: 60,70,80,90

b>Usual Delivery Time or Lead Time: 0 to 15 business Days

br>

Shipping Type: Fedex or UPS Package

Fl