



General Characteristics of H1D Series Electromechanical De-Humidistat

The H1D Series is an electromechanical de-humidistat model control. Used for industrial and commercial use.
 For indoor use for spot heating.
 This is a heat only product.
 4.4 Amp @ 120VAC.
 2.2 Amp @ 240VAC.
 50 VA @ 24VAC – 240VAC.
 10% - 60% relative humidity range
 40°F to 100°F Temperature Range,
 This product is Canadian Standards Association certified & UL/U-CL Listed.



Product Applications of H1D Series Electromechanical De-Humidistat

For Industrial and commercial environments.
 Utilized in warehouses, factories, and work areas.
 Ideal for spot heating of work areas.
 This is an indoor product.



Warranty of H1D Series Electromechanical De-Humidistat

Manufacturer's Limited Warranty: 1 Year.

Specific Characteristics of H1D Series Electromechanical De-Humidistat

Item #	Manufacturing #	4.4 Amperes A	2.2 Amperes A	50 Volt-Ampere VA	Relative Humidity RH	Temp. Range (°F)	Weight and Dimensions with Packaging	
							Lbs.	L,W,H In.
USDHS-001	H1D1AA	120V	240V	24-240VAC	10-60%	40-100	4	3,5,7

Dimensions (In.) of H1D Series Electromechanical De-Humidistat

Series	Length A	Width B	Height C
USDHS-001	1"	3"	5"





Short Description of H1D Series Electromechanical De-Humidistat

Item #	Manufacturing #	Short Description 70 Characters Maximum
		1234567890123456789012345678901234567890123456789012345678901234567890

USDHS-001 H1D1AA 4.4A 120V, 2.2A 240V, 50VA 24-240VAC, Rh 10-60% Temp. Range 40-100°F.

SEO Table of H1D Series Electromechanical De-Humidistat

Title
TPI H1D Series Electromechanical De-Humidistat.
Meta Description
TPI H1D Series Electromechanical De-Humidistat Louver for Commercial Use, TPI H1D Series Electromechanical De-Humidistat for Industrial Use, TPI H1D Series Electromechanical De-Humidistat for indoor Use, TPI H1D Series Electromechanical De-Humidistat for Spot Heating Use.
Meta Key Words
TPI H1D Series Electromechanical De-Humidistat Louver for Commercial Use, TPI H1D Series Electromechanical De-Humidistat for Industrial Use, TPI H1D Series Electromechanical De-Humidistat for indoor Use, TPI H1D Series Electromechanical De-Humidistat for Spot Heating Use.
Meta URL (file name)
tpi-h1d-series-electromechanical-de-humidistat-us-english.htm

Product Line Description of H1D Series Electromechanical De-Humidistat

```
<FONT Size=1>
<b>Product Description:</b> TPI H1D Series Electromechanical De-Humidistat<br>
<b>Weather Rating:</b> Indoor<br>
<b>Amperes:</b> 2.2 & 4.4A<br>
<b>Volt-Amperes:</b> 50VA<br>
<b>Voltage:</b> 120,240 & 24-240V<br>
<b>Relative Humidity:</b> 10-60%<br>
<b>Temp. Range (°F):</b> 40-100°F<br>
<b>Product Type:</b> TPI H1D Series Electromechanical De-Humidistat<br>
<b>Usual Delivery Time or Lead Time:</b> 1 to 2 weeks<br>
</FONT>
```