

General Characteristics of HLT Series Hazardous Location Thermostats & Controls

The HLT Series is a hazardous location line voltage thermostat. Includes Celsius & Fahrenheit Scale, and is heat or cool compatible. Used in industrial and commercial environments. Is for indoor spot heating use. Comes with bi-metal or capillary sensor and snap action switch. Works with DPDT (Double Pole Double Throw) & SPDT (Single Pole Double Throw.) The casting is tapered top and bottom for 3/4" conduit. Made with a 1/2" thick cast Aluminum housing. This product is UL/U-CL Listed. NEMA class seven Div. 1 Approved. Motor Rating (full load): 3/4 HP @ 125V, 1-1/2 HP @ 250V. Class I group C & D, class II group E, F & G. Not rated for group B. The HLT series incorporate plastic knob & bi-metal sensor housing.



Product Applications of HLT Series Hazardous Location Thermostats & Controls

For industrial and commercial environments. Utilized in warehouses, factories, and work areas for spot heating. This is an Indoor Product.



Warranty of HLT Series Hazardous Location Thermostats & Controls


Manufacturer's Limited Warranty: 1 Year.

Specific Characteristics of HLT Series Hazardous Location Thermostats & Controls

Item #	Manufacturing #	Description	Load Rating	Range (°F)	Weight and Dimensions with Packaging	
					Lbs.	L,W,H In.
USHLT-001	HLT-1	SPDT Capillary	22A@120-227VAC	40-100	5	7,7,8
USHLT-002	HLT-2	DPDT Capillary	22A@120-227VAC	40-100	5	7,7,8


Dimensions (In.) of HLT Series Hazardous Location Thermostats & Controls

Series	Length A	Width B	Height C
All USHLT Series	5 3/4"	5.57"	6 3/8"





Ecological HVAC Supply & Engineering
 1-888-514-1516, (626) 771-0048, F: (626) 771-0047
 sales@ventdepot.com www.VentDepot.com



TPI Corporation
 America's Comfort Conditioning Company

**HLT Series
 Hazardous Location
 Thermostats & Controls
 Data Sheet**

Short Description of HLT Series Hazardous Location Thermostats & Controls

Item #	Manufacturing #	Short Description 70 Characters Maximum
		0123456789012345678901234567890123456789012345678901234567890123456789
USHLT-001	HLT-1	SPDT Capillary, 22A120-227VAC, 40°-100°.

SEO Table of HLT Series Hazardous Location Thermostats & Controls

Title
TPI HLT Series Hazardous Location Thermostats & Controls.
Meta Description
TPI HLT Series Hazardous Location Thermostats & Controls for Industrial Use, TPI HLT Series Hazardous Location Thermostats & Controls for Commercial Use, TPI HLT Series Hazardous Location Thermostats & Controls for Indoor Use, TPI HLT Series Hazardous Location Thermostats & Controls Spot Heating Use.
Meta Key Words
TPI HLT Series Hazardous Location Thermostats & Controls for Industrial Use, TPI HLT Series Hazardous Location Thermostats & Controls for Commercial Use, TPI HLT Series Hazardous Location Thermostats & Controls for Indoor Use, TPI HLT Series Hazardous Location Thermostats & Controls Spot Heating Use.
Meta URL (file name)
Tpi-HLT-series-hazardous-location-thermostats-and-controls-us-english.htm

Product Line Description of Fan Forced Portable Heater 178 Series

```
<FONT Size=1>
<b>Product Description:</b> TPI HLT Series Hazardous Location Thermostats & Controls<br>
<b>Weather Rating:</b> Indoor<br>
<b>Description:</b> DPDT Capillary & SPDT Capillary<br>
<b>Voltage:</b> 22A@120-227VAC<br>
<b>Temp. Range (°F):</b> 40°-100°<br>
<b>Product Type:</b> TPI HLT Series Hazardous Location<br>
<b>Usual Delivery Time or Lead Time:</b> 1 to 2 weeks<br>
</FONT>
```