

**General Characteristics of JetAire Oscillating Ceiling Direct Drive Fan**

The JetAire Oscillating is a high velocity, direct drive fan. Is for industrial, commercial and golf course use. Used both indoor and outdoors. These units are super air moving devices with a concentrated air flow at high velocity reaching distances of 100 feet or more. For desired directional airflow units come with tiltable head. Manufactured in a durable polypropylene barrels and equipped with totally enclosed motors. Oscillator available in 115, 230 or 460V. Available in hunter green or an industrial gray housing. Optional misting kits are available for added comfort, as well as pedestal bases. Sold separately. All units meet OSHA requirements. Made in the USA.

**Product Applications of JetAire Oscillating Ceiling Direct Drive Fan**

Recommended for Commercial Buildings. For indoor and outdoor use. Perfect for areas where located air flow is required. Also suitable for most operations in dusty or moist environments.

**Warranty of JetAire Oscillating Ceiling Direct Drive Fan**

Includes Manufacturer's Limited Warranty: 1 Year



**Specific Characteristics of JetAire Oscillating Ceiling Direct Drive Fan**

Item#	Manufacturing #	Dia. (In.)	CFM	Volts V	Amps A	Phases Ph	HP	Mounting bracket	Motor Type	Weight and Dimensions with Packaging	
										Lbs.	L,W,H In.
<b>USOAO-001</b>	HV2413OC-V + VMB2430-OSC	24	5,600	115	4	1	1/2	Vertical	Enclosed	216	36,25,49
<b>USOAO-002</b>	HV2413OC-W + VMB2430-OSC	24	5,600	230	2	1	1/2	Vertical	Enclosed	216	36,25,49
<b>USOAO-003</b>	HV2413OC-Y + VMB2430-OSC	24	5,600	230	1.16	3	1/2	Vertical	Enclosed	216	36,25,49
<b>USOAO-004</b>	HV2413OC-Z + VMB2430-OSC	24	5,600	460	0.578	3	1/2	Vertical	Enclosed	216	36,25,49
<b>USOAO-005</b>	HV2415OC-V + VMB2430-OSC	24	5,900	115	8.01	1	1	Vertical	Enclosed	221	36,25,49
<b>USOAO-006</b>	HV2415OC-W + VMB2430-OSC	24	5,900	230	4	1	1	Vertical	Enclosed	221	36,25,49
<b>USOAO-007</b>	HV2415OC-Y + VMB2430-OSC	24	5,900	230	2.31	3	1	Vertical	Enclosed	221	36,25,49
<b>USOAO-008</b>	HV2415OC-Z + VMB2430-OSC	24	5,900	460	1.16	3	1	Vertical	Enclosed	221	36,25,49
<b>USOAO-009</b>	HV3013OC-V + VMB2430-OSC	30	7,900	115	4	1	1/2	Vertical	Enclosed	226	42,25,54
<b>USOAO-010</b>	HV3013OC-W + VMB2430-OSC	30	7,900	230	2	1	1/2	Vertical	Enclosed	226	42,25,54



Item#	Manufacturing #	Dia. (In.)	CFM	Volts V	Amps A	Phases Ph	HP	Mounting bracket	Motor Type	Weight and Dimensions with Packaging	
										Lbs.	L,W,H In.
<b>USOAO-011</b>	HV3013OC-Y + VMB2430-OSC	30	7,900	230	1.16	3	1/2	Vertical	Enclosed	226	42,25,54
<b>USOAO-012</b>	HV3013OC-Z + VMB2430-OSC	30	7,900	460	0.578	3	1/2	Vertical	Enclosed	226	42,25,54
<b>USOAO-013</b>	HV3015OC-V + VMB2430-OSC	30	10,600	115	8.01	1	1	Vertical	Enclosed	265	42,25,54
<b>USOAO-014</b>	HV3015OC-W + VMB2430-OSC	30	10,600	230	4	1	1	Vertical	Enclosed	265	42,25,54
<b>USOAO-015</b>	HV3015OC-Y + VMB2430-OSC	30	10,600	230	2.31	3	1	Vertical	Enclosed	265	42,25,54
<b>USOAO-016</b>	HV3015OC-Z + VMB2430-OSC	30	10,600	460	1.16	3	1	Vertical	Enclosed	265	42,25,54

### Dimensions (In.) of JetAire Oscillating Ceiling Direct Drive Fan

Series	Length A	Width B	Height C
USOAO-001 to 008	30"	09"	30"
USOAO-009 to 016	34"	09"	34"

### Dimensions Diagram of JetAire Oscillating Ceiling Direct Drive Fan

