



### General Characteristics of JetFoot Pedestal Non-Oscillating Direct Drive Fan

The JetFoot Pedestal Non-Oscillating direct drive fan is a high velocity unit.

Is for industrial, commercial and golf course use  
 Used both indoor and outdoors.

These units are super air moving devices with a concentrated air flow at high velocity reaching distances of 100 feet or more.

Comes with Pedestal mounting bracket.

For desired directional airflow units come with tiltable head.

Manufactured in a durable polypropylene barrels and equipped with totally enclosed motors.

Oscillator available in 115, 230 or 460V.

Available in hunter green or an industrial gray housing

Optional misting kits are available for added comfort, as well as pedestal bases. Sold separately

All units meet OSHA requirements.

Made in the USA.



### Product Applications of JetFoot Pedestal Non-Oscillating Direct Drive Fan

Recommended for Commercial Buildings.

For indoor and outdoor use.

Perfect for areas where located air flow is required. Also suitable for most operations in dusty or moist environments.

### Warranty of JetFoot Pedestal Non-Oscillating Direct Drive Fan

Includes Manufacturer's Limited Warranty: 1 Year

### Specific Characteristics of JetFoot Pedestal Non-Oscillating Direct Drive Fan

Item#	Manufacturing #	Dia. (In.)	CFM	Volts V	Amps A	Phases Ph	HP	Mounting bracket	Motor Type	Weight and Dimensions with Packaging	
										Lbs.	L,W,H In.
<b>USOAS-001</b>	HV2413-V + PB2430	24	5,600	115	4	1	1/2	Pedestal	Enclosed	216	36,25,49
<b>USOAS-002</b>	HV2413-W + PB2430	24	5,600	230	2	1	1/2	Pedestal	Enclosed	216	36,25,49
<b>USOAS-003</b>	HV2413-Y + PB2430	24	5,600	230	1.16	3	1/2	Pedestal	Enclosed	216	36,25,49
<b>USOAS-004</b>	HV2413-Z + PB2430	24	5,600	460	0.578	3	1/2	Pedestal	Enclosed	216	36,25,49
<b>USOAS-005</b>	HV2415-V + PB2430	24	5,900	115	8.01	1	1	Pedestal	Enclosed	221	36,25,49
<b>USOAS-006</b>	HV2415-W + PB2430	24	5,900	230	4	1	1	Pedestal	Enclosed	221	36,25,49
<b>USOAS-007</b>	HV2415-Y + PB2430	24	5,900	230	2.31	3	1	Pedestal	Enclosed	221	36,25,49
<b>USOAS-008</b>	HV2415-Z + PB2430	24	5,900	460	1.16	3	1	Pedestal	Enclosed	221	36,25,49
<b>USOAS-009</b>	HV3013-V + PB2430	30	7,900	115	4	1	1/2	Pedestal	Enclosed	226	42,25,54



**USOAS-010** HV3013-W + PB2430 30 7,900 230 2 1 1/2 Pedestal Enclosed 226 42,25,54

Item#	Manufacturing #	Dia. (In.)	CFM	Volts V	Amps A	Phases Ph	HP	Mounting bracket	Motor Type	Weight and Dimensions with Packaging	
										Lbs.	L,W,H In.
<b>USOAS-011</b>	HV3013-Y + HMB2430	30	7,900	230	1.16	3	1/2	Pedestal	Enclosed	226	42,25,54
<b>USOAS-012</b>	HV3013-Z + HMB2430	30	7,900	460	0.578	3	1/2	Pedestal	Enclosed	226	42,25,54
<b>USOAS-013</b>	HV3015-V + HMB2430	30	10,600	115	8.01	1	1	Pedestal	Enclosed	265	42,25,54
<b>USOAS-014</b>	HV3015-W + HMB2430	30	10,600	230	4	1	1	Pedestal	Enclosed	265	42,25,54
<b>USOAS-015</b>	HV3015-Y + HMB2430	30	10,600	230	2.31	3	1	Pedestal	Enclosed	265	42,25,54
<b>USOAS-016</b>	HV3015-Z + HMB2430	30	10,600	460	1.16	3	1	Pedestal	Enclosed	265	42,25,54

### Dimensions (In.) of JetFoot Pedestal Non-Oscillating Direct Drive Fan

Series	Length A	Width B	Height C
USOAS-001 to 008	30"	09"	30"
USOAS-009 to 016	34"	09"	34"

### Dimensions Diagram of JetAire Pedestal Non-Oscillating Direct Drive Fan

