## **VentDepot**

Ecological HVAC Supply & Engineering 1-888-514-1516, (626) 771-0048, F: (626) 771-0047 sales@ventdepot.com www.VentDepot.com



## **MB-DY Series**

## Industrial Mini-Blowers

General Characteristics of MB-DY Series Industrial Mini-Blowers.

Comes in sizes 24" & 30"

SJT type 3 conductor, 10' long cord

Aluminum, 3 paddle Blade

Spiral, wire front and rear guards

Corrosion and dent proof high density polyethylene housing

Meets OSHA standards

CFM measured 2 feet from face of fan

1 Year limited warranty

Made in the U.S.A.

Motor Specifications

1-Phase

¼ HP

2-Speed

Totally enclosed, permanently lubricated Permanent split capacitor

Ball bearing

Totally enclosed motor allows mini-blower to be used in dirty or dusty environments.

Available as floor model or yoke mounted model that can be directly bolted to any Surface or used with optional wall/ceiling mount.

### Product Applications of MB-DY Series Industrial Mini-Blowers.

#### For industrial and commercial use.

Used for cooling factories, shops, bakeries, loading, docks, laundries, gymnasiums, warehouses, aircraft hangars, and virtually any place a high volumen of air movement is required.

#### For indoor use.

#### Warranty of MB-DY Series Industrial Mini-Blowers.

Manufacturer's Warranty: 1 year.





|           | S               | Specifi | c Charact | eristics of | of ME | B-DY Se        | eries Ind | dus | trial Mini-Blow   | vers.        |   |           |
|-----------|-----------------|---------|-----------|-------------|-------|----------------|-----------|-----|-------------------|--------------|---|-----------|
| ltem #    | Manufacturing # | Size    | CFM/RPM   |             | Volts | Amperes Phases |           | HP  | CFM/Area Sq Ft    | Type         | Weight and Dimensions with<br>Packaging |           |
|           |                 | Ø(ln.)  | High      | Low         | V     | А              | PH        |     | or withica oq i t | туре         | Lbs.                                    | L,W,H In. |
| USMBY-001 | MB24-DY         | 24      | 3300/1140 | 2900/1070   | 120   | 1.8            | 1         | 1⁄4 | 5200/240          | Yoke Style   | 54                                      | 37x30x17  |
| USMBY-002 | MB24-DY+MBM-W   | 24      | 3300/1140 | 2900/1070   | 120   | 1.8            | 1         | 1⁄4 | 5200/240          | Wall/Ceiling | 54                                      | 37x30x17  |
| USMBY-003 | MB30-DY         | 30      | 4400/1040 | 3900/730    | 120   | 2.7            | 1         | 1⁄4 | 7000/250          | Yoke Style   | 60                                      | 38x36x18  |
| USMBY-004 | MB30-DY+ MBM-W  | 30      | 4400/1040 | 3900/730    | 120   | 2.7            | 1         | 1⁄4 | 7000/250          | Wall/Ceiling | 60                                      | 38x36x18  |







## **VentDepot**


Ecological HVAC Supply & Engineering 1-888-514-1516, (626) 771-0048, F: (626) 771-0047 sales@ventdepot.com www.VentDepot.com


# TPI Corporation MB-DY Series


#### **Industrial Mini-Blowers**

Data Sheet

| Dimensions (In.) of MB-DY Series Industrial Mini-Blowers |        |        |       |  |  |  |  |  |  |
|--|--------|--------|-------|--|--|--|--|--|--|
| Series   | Length | Height | Width |  |  |  |  |  |  |
| Selles   | A      | В      | С     |  |  |  |  |  |  |
| USMBY-001 to USMBY-002                                   | 29"    | 28 ½"  | 14 ¼" |  |  |  |  |  |  |
| USMBY-003 to USMBY-004                                   | 38"    | 37 ½"  | 14 ¼" |  |  |  |  |  |  |
| <b>Optional Wall/Ceiling Mount</b>                       | 10"    | 8"     |       |  |  |  |  |  |  |







**VentDepot** • §

Aire Acondicionado, Ventilación y Calefacción Ecológica Call Center Nacional: 01 800 999. 1516 Call Center México: (55) 5822.1516 Tienda: www.VentDepot.com E-mail: ventas@ventdepot.com









Ecological HVAC Supply & Engineering 1-888-514-1516, (626) 771-0048, F: (626) 771-0047 sales@ventdepot.com www.VentDepot.com



Data Sheet

**Gallery of MB-DY Series Industrial Mini-Blowers** 

