



General Characteristics of MCD Series Medium Stand Industrial Direct Drive Blowers

The MCD Series motors come in two options totally enclosed and explosion proof.
 Can be used in industrial or commercial areas.
 For indoor or outdoor use.
 Used for cooling and high volume air movement.
 The blades are made of cast aluminum; the body and stand are made from 14 gauge steel.
 This product comes with the option of an acid resistant coating.
 For Safety the CPB Series are designed with spiral wire front and rear guards.
 Finished off with a baked enamel coating.
 The high and medium stand units have a 360° swivel
 Single phase motors are field convertible 115V/230V.
 Three phase motors are field convertible 230V/460V.
 Motors are set to lower voltage at the factory unless a request is made at the time of order to set to the higher voltage.
 Note: products listed are custom built and subject to 100% cancellation/restocking charges.
 The MCD Series meets OSHA requirements.
 Imported to TPI specifications.



Product Applications of MCD Series Medium Stand Industrial Direct Drive Blowers

For industrial and commercial use.
 Used for cooling factories, shops, bakeries, loading docks, laundries, gymnasiums, warehouses, aircraft hangars, and virtually any place a high volume of air movement is required.
 For indoor and outdoor use.

Warranty of MCD Series Medium Stand Industrial Direct Drive Blowers

Manufacturer's Warranty: 1 year.

Specific Characteristics of MCD Series Medium Stand Industrial Direct Drive Blowers

Item #	Manufacturing #	Size Ø(In.)	CFM	Volts	Amperes A	Phases Ph	HP	RPM	DB'S	Stand Type	Weight and Dimensions with Packaging	
											Lbs.	L,W,H In.
USMSB-001	MCD18-1/4-M	18	3050	115/230	2.25/1.13	1	1/4	1725	74	Medium Stand	147	34,25,40
USMSB-002	MCD18-1/4-M-3	18	3050	230/460	0.73/0.36	3	1/4	1725	74	Medium Stand	147	34,25,40



USMSB-003	MCD18-1/3-M	18	3450	115/230	2.97/1.49	1	1/3	1725	76	Medium Stand	152	34,25,40
USMSB-004	MCD18-1/3-M-3	18	3450	230/460	0.95/0.74	3	1/3	1725	76	Medium Stand	152	34,25,40
USMSB-005	MCD18-1-M	18	4600	115/230	9.01/4.5	1	1	1725	77	Medium Stand	167	34,25,40
USMSB-006	MCD18-1-M-3	18	4600	230/460	2.89/1.45	3	1	1725	77	Medium Stand	167	34,25,40

Item #	Manufacturing #	Size Ø(In.)	CFM	Volts	Amperes A	Phases Ph	HP	RPM	DB'S	Stand Type	Weight and Dimensions with Packaging	
											Lbs.	L,W,H In.
USMSB-007	MCD24-1/4-M	24	5200	115/230	2.25/1.13	1	1/4	1725	80	Medium Stand	167	34,31,43
USMSB-008	MCD24-1/4-M-3	24	5200	230/460	0.73/0.36	3	1/4	1725	80	Medium Stand	167	34,31,43
USMSB-009	MCD24-1/3-M	24	5300	115/230	2.97/1.49	1	1/3	1140	74	Medium Stand	177	34,31,43
USMSB-010	MCD24-1/3-M-3	24	5300	230/460	0.95/0.74	3	1/3	1140	74	Medium Stand	177	34,31,43
USMSB-011	MCD24-1/2-M	24	6000	115/230	4.5/2.25	1	1/2	1725	80	Medium Stand	172	34,31,43
USMSB-012	MCD24-1/2-M-3	24	6000	230/460	1.45/0.73	3	1/2	1725	80	Medium Stand	172	34,31,43
USMSB-013	MCD24-3/4-M	24	6900	115/230	6.76/3.38	1	3/4	1140	74	Medium Stand	192	34,31,43
USMSB-014	MCD24-3/4-M-3	24	6900	230/460	2.16/1.09	3	3/4	1140	74	Medium Stand	192	34,31,43
USMSB-015	MCD24-1-M	24	7400	115/230	9.01/4.5	1	1	1725	82	Medium Stand	182	34,31,43
USMSB-016	MCD24-1-M-3	24	7400	230/460	2.89/1.45	3	1	1725	82	Medium Stand	182	34,31,43
USMSB-017	MCD24-1 1/2-M	24	8200	115/230	13.5/6.76	1	1 ½	1725	84	Medium Stand	192	34,31,43
USMSB-018	MCD24-1 1/2-M-3	24	8200	230/460	4.34/2.16	3	1 ½	1725	84	Medium Stand	192	34,31,43
USMSB-019	MCD24-3-M-3	24	10500	230/460	8.68/4.34	3	3	1725	87	Medium Stand	215	34,31,43
USMSB-020	MCD30-1/3-M	30	6900	115/230	2.97/1.49	1	1/3	1140	80	Medium Stand	210	34,37,46
USMSB-021	MCD30-1/3-M-3	30	6900	230/460	0.95/0.74	3	1/3	1140	80	Medium Stand	210	34,37,46
USMSB-022	MCD30-1/2-M	30	8900	115/230	4.5/2.25	1	1/2	1725	86	Medium Stand	197	34,37,46
USMSB-023	MCD30-1/2-M-3	30	8900	230/460	1.45/0.73	3	1/2	1725	86	Medium Stand	197	34,37,46
USMSB-024	MCD30-3/4-M	30	10400	115/230	6.76/3.38	1	3/4	1140	80	Medium Stand	265	34,37,46
USMSB-025	MCD30-3/4-M-3	30	10400	230/460	2.16/1.09	3	3/4	1140	80	Medium Stand	265	34,37,46
USMSB-026	MCD30-1-M	30	11200	115/230	9.01/4.5	1	1	1140	81	Medium Stand	265	34,37,46
USMSB-027	MCD30-1-M-3	30	11200	230/460	2.89/1.45	3	1	1140	81	Medium Stand	265	34,37,46
USMSB-028	MCD30-1 1/2-M	30	12000	115/230	13.5/6.76	1	1 ½	1725	92	Medium Stand	255	34,37,46
USMSB-029	MCD30-1 1/2-M-3	30	12000	230/460	4.34/2.16	3	1 ½	1725	92	Medium Stand	255	34,37,46
USMSB-030	MCD30-2-M-3	30	14000	230/460	5.78/2.89	3	2	1140	84	Medium Stand	275	34,37,46
USMSB-031	MCD30-3-M-3	30	16000	230/460	8.68/4.34	3	3	1725	94	Medium Stand	270	34,37,46
USMSB-032	MCD36-1-M	36	13000	115/230	9.01/4.5	1	1	1140	82	Medium Stand	325	34,43,47
USMSB-033	MCD36-1-M-3	36	13000	230/460	2.89/1.45	3	1	1140	82	Medium Stand	325	34,43,47
USMSB-034	MCD36-1 1/2-M	36	14850	115/230	13.5/6.76	1	1 ½	1725	88	Medium Stand	325	34,43,47
USMSB-035	MCD36-1 1/2-M-3	36	14850	230/460	4.34/2.16	3	1 ½	1725	88	Medium Stand	325	34,43,47
USMSB-036	MCD36-2-M-3	36	17500	230/460	5.78/2.89	3	2	1140	82	Medium Stand	330	34,43,47
USMSB-037	MCD36-3-M-3	36	18500	230/460	8.68/4.34	3	3	1725	90	Medium Stand	335	34,43,47
USMSB-038	MCD36-5-M-3	36	23000	230/460	14.5/7.23	3	5	1725	94	Medium Stand	335	34,43,47
USMSB-039	MCD42-2-M-3	42	19500	230/460	5.78/2.89	3	2	1140	85	Medium Stand	420	34,49,50
USMSB-040	MCD42-5-M-3	42	27000	230/460	14.5/7.23	3	5	1725	98	Medium Stand	425	34,49,50
USMSB-041	MCD48-5-M-3	48	32000	230/460	14.5/7.23	3	5	1140	92	Medium Stand	625	34,55,63
USMSB-042	MCD48-7 1/2-M-3	48	37000	230/460	21.6/10.8	3	7 ½	1140	105	Medium Stand	750	34,55,63
USMSB-043	MCD48-10-M-3	48	41000	230/460	28.9/14.5	3	10	1140	105	Medium Stand	805	34,55,63
USMSB-044	MCD60-3-M-3	60	35000	230/460	8.68/4.34	3	3	690	87	Medium Stand	860	58,69,89
USMSB-045	MCD60-5-M-3	60	45000	230/460	14.5/7.23	3	5	690	87	Medium Stand	900	58,69,89
USMSB-046	MCD60-7 1/2-M-3	60	47000	230/460	21.6/10.8	3	7 ½	870	90	Medium Stand	1115	58,69,89
USMSB-047	MCD60-10-M-3	60	57200	230/460	28.9/14.5	3	10	870	91	Medium Stand	1205	58,69,89
USMSB-048	MCD60-15-M-3	60	60750	230/460	43.4/21.6	3	15	870	92	Medium Stand	1250	58,69,89



Dimensions (In.) of MCD Series Medium Stand Industrial Direct Drive Blowers

Series	Length A	Width B	Height C
USMSB-001 to 006	32"	23 1/2"	38"
USMSB-007 to 019	32"	29 1/2"	41"
USMSB-020 to 031	32"	35 1/2"	44"
USMSB-032 to 038	32"	41 1/2"	47"
USMSB-039 & 040	32"	47 1/2"	50"
USMSB-041 to 043	32"	53 1/2"	61 1/2"
USMSB-044 to 048	56"	67"	87 1/2"

