



### General Characteristics of RV Series Belt Drive Intake Wall Fan

The RV Series is a belt-driven intake wall fan, and is designed with long lasting performance in mind.

It can be used in industrial or commercial areas.

For indoor use.

The RV series ranges from 24" to 48" units.

These units come standard with automatic belt tensioning, to reduce maintenance and extend the belt and motors.

Made with rolled venturi for improved airflow, as well as high-quality heavy-duty components, and finished off with a durable polyester powder-coated finish.

Note: All products listed are in this section are custom built and subject to 100% cancellation/restocking charges.

The photograph is a representation of stocked models actual models may vary in appearance.



### Product Applications of RV Series Belt Drive Intake Wall Fan

For industrial and commercial use.

Used for cooling factories, shops, bakeries, loading docks, laundries, gymnasiums, warehouses, aircraft hangars, and virtually any place a high volume of air movement is required.

For indoor use.

### Warranty of RV Series Belt Drive Intake Wall Fan

Manufacturer's Warranty: 1 year.

### Specific Characteristics of RV Series Belt Drive Intake Wall Fan

Item #	Manufacturing #	Size (In.)	CFM			Volts V	Amps A	Phase Ph	HP	Drive Type	Motor Type	Weight and Dimensions with Packaging	
			0.0SP	0.125SP	0.25SP							Lbs.	L,W,H In.
USBUK-001	RV2412-V	24	3,920	2,070	930	115	2.64	1	1/3	Belt	Open	55	32,19,32
USBUK-002	RV3012-V	30	6,420	4,980	1,790	115	2.64	1	1/3	Belt	Open	57	36,19,36
USBUK-003	RV3013-V	30	9,560	7,770	4,850	115	4	1	1/2	Belt	Open	70	36,19,36
USBUK-004	RV3013T-U	30	9,560	7,770	4,850	115/230	4/2	1	1/2	Belt	Enclosed	70	36,19,36
USBUK-005	RV3013-X	30	9,560	7,770	4,850	230/460	1.16/0.578	3	1/2	Belt	Open	70	36,19,36
USBUK-006	RV3613-V	36	10,900	9,160	4,310	115	4	1	1/2	Belt	Open	73	42,19,42
USBUK-007	RV3613T-U	36	10,900	9,160	4,310	115/230	4/2	1	1/2	Belt	Enclosed	73	42,19,42
USBUK-008	RV3613-X	36	10,900	9,160	4,310	230/460	1.16/0.578	3	1/2	Belt	Open	73	42,19,42
USBUK-009	RV4213-V	42	14,200	11,600	5,470	115	4	1	1/2	Belt	Open	92	48,19,48
USBUK-010	RV4213T-U	42	14,200	11,600	5,470	115/230	4/2	1	1/2	Belt	Enclosed	92	48,19,48
USBUK-011	RV4213-X	42	14,200	11,600	5,470	230/460	1.16/0.578	3	1/2	Belt	Open	92	48,19,48
USBUK-012	RV4813-V	48	17,100	11,500	3,900	115	4	1	1/2	Belt	Open	108	54,19,54
USBUK-013	RV4813T-U	48	17,100	11,500	3,900	115/230	4/2	1	1/2	Belt	Enclosed	108	54,19,54
USBUK-014	RV4813-X	48	17,100	11,500	3,900	230/460	1.16/0.578	3	1/2	Belt	Open	108	54,19,54
USBUK-015	RV4814-U*	48	18,100	13,800	6,370	115/230	6.01/3	1	3/4	Belt	Open	112	54,19,54

\*Duel Voltage, Single Phase and Prewired 115V



**Dimensions (In.) of RV Series Belt Drive Intake Wall Fan**

Series	Length A	Width B	Height C
USBUK-001	30"	16 1/4"	30"
USBUK-002	34"	16 1/4"	34"
USBUK-003	40"	16 1/4"	40"
USBUK-004	46"	16 1/4"	46"
USBUK-005	52"	16 1/4"	52"

