



General Characteristics of RV Series Belt Drive Intake Wall Fan

The RV Series is a belt-driven intake wall fan, and is designed with long lasting performance in mind.

It can be used in industrial or commercial areas.

For indoor use.

The RV series ranges from 24" to 48" units.

These units come standard with automatic belt tensioning, to reduce maintenance and extend the belt and motors.

Made with rolled venturi for improved airflow, as well as high-quality heavy-duty components, and finished off with a durable polyester powder-coated finish.

Note: All products listed are in this section are custom built and subject to 100% cancellation/restocking charges.

The photograph is a representation of stocked models actual models may vary in appearance.



Product Applications of RV Series Belt Drive Intake Wall Fan

For industrial and commercial use.

Used for cooling factories, shops, bakeries, loading docks, laundries, gymnasiums, warehouses, aircraft hangars, and virtually any place a high volume of air movement is required.

For indoor use.

Warranty of RV Series Belt Drive Intake Wall Fan

Manufacturer's Warranty: 1 year.

Specific Characteristics of RV Series Belt Drive Intake Wall Fan

| Item # | Manufacturing # | Size (In.) | CFM | | | Volts V | Amps A | Phase Ph | HP | Drive Type | Motor Type | Weight and Dimensions with Packaging | |
|-----------|-----------------|------------|--------|---------|--------|---------|------------|----------|-----|------------|------------|--------------------------------------|-----------|
| | | | 0.0SP | 0.125SP | 0.25SP | | | | | | | Lbs. | L,W,H In. |
| USBUU-001 | RV2412-V | 24 | 3,920 | 2,070 | 930 | 115 | 2.64 | 1 | 1/3 | Belt | Open | 55 | 32,19,32 |
| USBUU-002 | RV3012-V | 30 | 6,420 | 4,980 | 1,790 | 115 | 2.64 | 1 | 1/3 | Belt | Open | 57 | 36,19,36 |
| USBUU-003 | RV3013-V | 30 | 9,560 | 7,770 | 4,850 | 115 | 4 | 1 | 1/2 | Belt | Open | 70 | 36,19,36 |
| USBUU-004 | RV3013T-U | 30 | 9,560 | 7,770 | 4,850 | 115/230 | 4/2 | 1 | 1/2 | Belt | Enclosed | 70 | 36,19,36 |
| USBUU-005 | RV3013-X | 30 | 9,560 | 7,770 | 4,850 | 230/460 | 1.16/0.578 | 3 | 1/2 | Belt | Open | 70 | 36,19,36 |
| USBUU-006 | RV3613-V | 36 | 10,900 | 9,160 | 4,310 | 115 | 4 | 1 | 1/2 | Belt | Open | 73 | 42,19,42 |
| USBUU-007 | RV3613T-U | 36 | 10,900 | 9,160 | 4,310 | 115/230 | 4/2 | 1 | 1/2 | Belt | Enclosed | 73 | 42,19,42 |



| | | | | | | | | | | | | | |
|------------------|-----------|----|--------|--------|-------|---------|------------|---|---|------|----------|-----|----------|
| USBUU-008 | RV3613-X | 36 | 10,900 | 9,160 | 4,310 | 230/460 | 1.16/0.578 | 3 | ½ | Belt | Open | 73 | 42,19,42 |
| USBUU-009 | RV4213-V | 42 | 14,200 | 11,600 | 5,470 | 115 | 4 | 1 | ½ | Belt | Open | 92 | 48,19,48 |
| USBUU-010 | RV4213T-U | 42 | 14,200 | 11,600 | 5,470 | 115/230 | 4/2 | 1 | ½ | Belt | Enclosed | 92 | 48,19,48 |
| USBUU-011 | RV4213-X | 42 | 14,200 | 11,600 | 5,470 | 230/460 | 1.16/0.578 | 3 | ½ | Belt | Open | 92 | 48,19,48 |
| USBUU-012 | RV4813-V | 48 | 17,100 | 11,500 | 3,900 | 115 | 4 | 1 | ½ | Belt | Open | 108 | 54,19,54 |
| USBUU-013 | RV4813T-U | 48 | 17,100 | 11,500 | 3,900 | 115/230 | 4/2 | 1 | ½ | Belt | Enclosed | 108 | 54,19,54 |
| USBUU-014 | RV4813-X | 48 | 17,100 | 11,500 | 3,900 | 230/460 | 1.16/0.578 | 3 | ½ | Belt | Open | 108 | 54,19,54 |
| USBUU-015 | RV4814-U* | 48 | 18,100 | 13,800 | 6,370 | 115/230 | 6.01/3 | 1 | ¾ | Belt | Open | 112 | 54,19,54 |

*Duel Voltage, Single Phase and Prewired 115V

Dimensions (In.) of RV Series Belt Drive Intake Wall Fan

| Series | Length A | Width B | Height C |
|-----------|-------------|------------|-------------|
| USBUU-001 | 30" | 16 1/4" | 30" |
| USBUU-002 | 34" | 16 1/4" | 34" |
| USBUU-003 | 40" | 16 1/4" | 40" |
| USBUU-004 | 46" | 16 1/4" | 46" |
| USBUU-005 | 52" | 16 1/4" | 52" |

