

General Characteristics

- ▶ The VentDepot SafeRoller is a practical, rugged, low-cost air mover used worldwide.
- ▶ Fans are equipped with a ONE speed explosion proof motor, aluminum fan blade assembly but WITHOUT switch or wiring.
- ▶ Motors supplied are Class I, Div. 1, Groups C & D and Class II, Div. 1, Groups F & G.
- ▶ Built with heavy gauge cold rolled steel barrels.
- ▶ Tough, rubber tread wheels.
- ▶ Spiral wound wire guard meets OSHA requirements.
- ▶ Attractive bronze powder coat finish.
- ▶ Frame is heavy duty tubing.
- ▶ Tilts 90° up or down with positive lock tilt control.

Product Applications

- ▶ It is used to cool factories, shops, bakeries, loading docks, laundries, gymnasiums, warehouses, aircraft hangars, and virtually any place a high volume of air movement is required.
- ▶ The fans portability allows it to be placed in convenient locations and can be easily put away for storage.
- ▶ CAUTION, WARNING: Although this product is supplied with an explosion proof motor and aluminum spark arresting fan blade, it is not intended to convey the suitability of the overall finished product in an explosive atmosphere, but only that the product has been supplied with certain components for this purpose. Wiring must be in accordance with local, state and national codes and be performed by a qualified electrician.



Warranty

- ▶ Manufacturer's Limited Warranty: 3 Years.

Specific Characteristics

Item #	Ø in.	CFM	RPM	V	A	Phase	HP	Drive Type	Motor Enclosure	Weight lbs	Shipping Size in. (W,H,L)
USEPT-001	36	12100	480	115	7.5	1	½	Belt	Explosion Proof	156	45,24,49
USEPT-002	36	12100/8060	480/336	115	7.5	1	½	Belt	Explosion Proof	156	45,24,49
USEPT-003	42	14445	525	115	7.5	1	½	Belt	Explosion Proof	193	52,25.5,54
USEPT-004	42	14445/9950	525/367	115	7.3	1	½	Belt	Explosion Proof	193	52,25.5,54
USEPT-005	42	16900	525	115	13.0	1	¾	Belt	Explosion Proof	193	52,25.5,54
USEPT-006	48	19460	500	155	11.0	1	1	Belt	Explosion Proof	251	57,26,62