

General Characteristics of Standard Mist Nozzles SauNozz

The Standard Mist Nozzles SauNozz are available in brass with stainless steel orifice sizes from .008" to .020" with flow rates from .020 gpm to .055 gpm.

The VentDepot Standard Mist Nozzles SauNozz spray patterns vary from 60 degrees to 90 degrees.

The VentDepot Standard Mist Nozzles SauNozz offers special order sizes and all stainless steel versions are also available.

Product Applications Standard Mist Nozzles SauNozz

The VentDepot Standard Mist Nozzles SauNozz spray patterns vary from 60 degrees to 90 degrees.

The VentDepot Standard Mist Nozzles SauNozz offers special order sizes and all stainless steel versions are also available.

Warranty of 50 Standard Mist Nozzles SauNozz

Manufacturer's Limited Warranty: 5 Years.



Specific Characteristics of Standard Mist Nozzles SauNozz

| VentDepot Item # | VentDepot Manufacturing # | Spray Nozzle Diameter | Description | O Ring Color | Material Type | Shipping Weight | | Shipping Size L,W,H | |
|------------------|---------------------------|-----------------------|----------------------------------|--------------|-------------------------|-----------------|-------|---------------------|-------|
| | | | | | | lbs | kg | in | cm |
| USSZZ-001 | 93508 | .008" | Nozzle x 10/24 Male UNC .020 GPM | Red | Brass & Stainless Steel | .006 | 0.002 | .4 x .375 x .375 | 1,1,1 |
| USSZZ-002 | 93512 | .012" | Nozzle x 10/24 Male UNC .029 GPM | Black | Brass & Stainless Steel | .006 | 0.002 | .4 x .375 x .375 | 1,1,1 |
| USSZZ-003 | 80450 | .016" | Nozzle x 10/24 Male UNC .044 GPM | Brown | Brass & Stainless Steel | .006 | 0.002 | .4 x .375 x .375 | 1,1,1 |
| USSZZ-004 | 93520 | .020" | Nozzle x 10/24 Male UNC .055 GPM | Green | Brass & Stainless Steel | .006 | 0.002 | .4 x .375 x .375 | 1,1,1 |

Image Gallery of Standard Mist Nozzles SauNozz



Standard Brass Nozzle .008" Orifice; .020 GPM; Red O-Ring
 USASAZ-001/93508



Standard Brass Nozzle .012" Orifice; .029 GPM; Black O-Ring
 USASAZ-002/93512



Brass Nozzle .016" Orifice; .044 GPM; Brown O-Ring
 USASAZ-003/80450



Standard Brass Nozzle .020" Orifice; .055 GPM; Green O-Ring
 USASAZ-004/93520

Short Description of Standard Mist Nozzles SauNozz

| VentDepot Item # | VentDepot Manufacturing # | Short Description 70 Characters Maximum | | | | | | | | | |
|------------------|---------------------------|---|---|---|---|---|---|---|---|---|---|
| | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 |
| USSZZ-001 | 93508 | .008" orifice which will produce .020 GPM with an 60° spray pattern at 1000 psi | | | | | | | | | |
| USSZZ-002 | 93512 | .012" orifice which will produce .029 GPM with an 70° spray pattern at 1000 psi | | | | | | | | | |
| USSZZ-003 | 80450 | .016" orifice which will produce .044 GPM with an 80° spray pattern at 1000 psi | | | | | | | | | |
| USSZZ-004 | 93520 | .020" orifice which will produce .055 GPM with an 90° spray pattern at 1000 psi | | | | | | | | | |

SEO Table of Standard Mist Nozzles SauNozz

| Title |
|---|
| Standard Mist Nozzles SauNozz |
| Meta Description |
| Standard Mist Nozzles SauNozz, Standard Mist Nozzles SauNozz for High Pressure Misting Systems, Standard Mist Nozzles SauNozz for Industrial Use, Standard Mist Nozzles SauNozz for Green Houses, Standard Mist Nozzles SauNozz for Commercial Use, Standard Misting Nozzles SauNozz for Restaurants, Standard Mist Nozzles SauNozz for Hotels, Standard Mist Nozzles SauNozz for Swimming Pools. |
| Meta Key Words |
| Standard Mist Nozzles SauNozz, Standard Mist Nozzles SauNozz for High Pressure Misting Systems, Standard Mist Nozzles SauNozz for Industrial Use, Standard Mist Nozzles SauNozz for Green Houses, Standard Mist Nozzles SauNozz for Commercial Use, Standard Misting Nozzles SauNozz for Restaurants, Standard Mist Nozzles SauNozz for Hotels, Standard Mist Nozzles SauNozz for Swimming Pools. |
| Meta URL (file name) |
| standard-mist-nozzles-saunozz-us-english.htm |

Product Line Description of Standard Mist Nozzles SauNozz

| |
|--|
| <pre> Product Description: Standard Mist Nozzles Use: Misting Systems Weather Rating: Indoor & Outdoor Gallons per Minute GPM: 0.020 to 0.055 Spray Degrees: 60,70,80,90 Usual Delivery Time or Lead Time: 0 to 15 business Days Shipping Type: Fedex or UPS Package </pre> |
|--|