



General Characteristics

- The VentDepot ShutMaster shutters are available from 24" to 60" square.
- These Shutters may be used with BusyExhaust, IndyExhaust, ExProofIndyExhaust, and other belt and direct drive fans; check for matching sizes.
- They open automatically for Exhaust fans only when the fan is turned on and close when the air flow stops.
- Shutter frames are heavy gauge steel with rigidly welded corners and finished with a tough, powder coat finish. Extruded aluminum shutter blades are attached with screws and durable bronze bushings to provide smooth operation without lubrication or maintenance.

Product Applications

Industrial and commercial use for Exhaust fans.

Warranty

Manufacturer's Limited Warranty: 3 Years.



Your HVAC/R Solution

Specific Characteristics							
Item #	Fan Size in.	Intake or Exhaust	Panel Type	Mount Type	Exterior Sizes L,W,H (in)	Interior Sizes L,W,H (in)	Weight lbs
USSMA-001	24	Exhaust	Single	Building Exterior	33-3/8,4,33-3/8	31,4,31	26
USSMA-002	30	Exhaust	Single	Building Exterior	36-3/8,4,36-3/8	34,4,34	29
USSMA-003	36	Exhaust	Single	To Fan Housing	39-3/8,4,39-3/8	37,4,37	33
USSMA-004	36	Exhaust	Single	Building Exterior	42-3/8,4,42-3/8	40,4,40	37
USSMA-005	42	Exhaust	Single	To Fan Housing	45-3/8,4,45-3/8	43,4,43	39
USSMA-006	42	Exhaust	Single	Building Exterior	48-3/8,4,48-3/8	46,4,46	46
USSMA-007	48	Exhaust	Single	To Fan Housing	51-3/8,4,51-3/8	49,4,49	43
USSMA-008	48	Exhaust	Single	Building Exterior	54-3/8,4,54-3/8	52,4,52	55
USSMA-009	54	Exhaust	Double	Building Exterior	63-3/8,4,63-3/8	61,4.5,61	45
USSMA-010	60	Exhaust	Double	Building Exterior	69-3/8,4,69-3/8	67,4.5,67	53