

General Characteristics of TPC HeatBuster Portable Barrel Fan

The TPC is a belt driven top of the line barrel fan. Can be used in industrial or commercial areas. For indoor use. Designed with an attractive heavy-duty tubing steel, wide body barrel. Finished off with a powder coating and a compact easy grip handle. Comes with an automatic belt tensioner. Units are 115, 60hz, single phase. With single or two speed. Motors are open drip proof or totally enclosed. Meeting OSHA requirements the SEB HeatBuster has a 10' grounded, 3 conductor cord with molded plug and spiral wound wire guards. All weights are approximate and may vary slightly.

Product Applications of TPC HeatBuster Portable Barrel Fan

It is used to cool factories, shops, bakeries, loading docks, laundries, gymnasiums, warehouses, aircraft hangars, and virtually any place a high volume of air movement is required. The fans portability allows it to be placed in convenient locations and can be easily put away for storage.

Warranty of TPC HeatBuster Portable Barrel Fan

Manufacturer's limited warranty in the US: 3 years. Warranty void if fan is left in rain or snow. These products are built to order, therefore they are non-returnable or non-refundable.



Specific Characteristics of TPC HeatBuster Portable Barrel Fan

Item #	Manufacturing #	Size Ø (In.)	CFM	Volts V	Amps A	Phases Ph	HP	RPM	Hz	Drive Type	Motor Type	Weight and Dimensions with Packaging	
												Lbs.	L,W,H In.
USFBP-001	TPC3613-T	36	12,100	115	7.6	1	½	500	60	Belt	Enclosed	145	23,42,44
USFBP-002	TPC4213-T	42	14,445	115	7.6	1	½	500	60	Belt	Enclosed	155	23,47,49
USFBP-003	TPC4214	42	15,850	115	13.0	1	¾	505	60	Belt	Open	157	27,47,49
USFBP-004	TPC4215	42	16,990	115	11.0	1	1	475	60	Belt	Open	195	27,47,49
USFBP-005	TPC4815	48	19,460	115	11.0	1	1	475	60	Belt	Open	517	27,42,54
USFBP-006	TPC6016	60	30,100	115	17.0	1	1 1/2	370	60	Belt	Open	244	27,65,70



Dimension (In.) of TPC HeatBuster Portable Barrel Fan

Series	Length A (In.)	Width B (In.)	Height C (In.)
USFBP-001	21"	40"	42"
USFBP-002	21"	45"	47"
USFBP-003 & 004	25"	25"	47"
USFBP-005	25"	25"	52"
USFBP-006	25"	25"	68"

