



**General Characteristics of Electric Wall or Ceiling Mounted Salamander YES Series**

Our YES Series has a Safety yellow heater enclosure with safety screens or both air intake and output openings. For indoor and outdoor use.

For outdoor use it may require an enclosure as it is not waterproof or rain-tight.

Is ETL-CETL listed

Long-life finned tubular heating elements.

Optional 25' long cord, ready for plug attachment is available for each model. Cords do not come with plug.

Thermostat adjustment 40° to 100° F.

High-limit thermal cutout switch / automatic reset.

Is the electric alternative to propane and kerosene space heaters.

800CFM: 9, 10 & 15Kw units. – 1100

CFM: 30Kw units.

Magnetic contactor.

Fan only operation feature.

Wall / ceiling bracket included with every unit.

All units are designed for direct wire installation.

Made in the U.S.A.

**Product Applications of Electric Wall or Ceiling Mounted Salamander YES Series**

Recommended for all industrial, commercial, and utility applications where portable high heat output is required.

Used frequently in construction, warehouses, loading docks, and workshops.

**Warranty of Electric Wall or Ceiling Mounted Salamander YES Series**

Manufacturer's Limited Warranty: 1 Year.



**Specific Characteristics of Electric Wall or Ceiling Mounted Salamander YES Series**

Item #	Manufacturing #	Kilowatts Kw	BTUs	Voltage V	Amperes A	Phase Ph	Temperature Rise (°F)	Cord Options	Weight and Dimensions with
--------	-----------------	--------------	------	-----------	-----------	----------	-----------------------	--------------	----------------------------



**YES Series**  
**Heat Wave Portable Electric & Wall**  
**Or Ceiling Mounted Salamander**  
Data Sheet

									packaging	
									Lbs.	W,H,L In.
<b>USTOT-001</b>	YES-1520-3A	15	51195	208	42	3	45°F	-	60	25,25,38
<b>USTOT-002</b>	YES-1520-3A + SO 6/4	15	51195	208	42	3	45°F	Cord	62	25,25,38
<b>USTOT-003</b>	YES-1524-1A	15	51195	240	42	1	45°F	-	60	25,25,40
<b>USTOT-004</b>	YES-1524-1A + SO 4/3	15	51195	240	42	1	45°F	Cord	62	25,25,40
<b>USTOT-005</b>	YES-1524-3E	15	51195	240	63	3	45°F	-	60	25,25,38
<b>USTOT-006</b>	YES-1524-3E + SO 6/4	15	51195	240	63	3	45°F	Cord	62	25,25,38
<b>USTOT-007</b>	YES-1548-3E	15	51195	480	36	3	45°F	-	60	25,25,38
<b>USTOT-008</b>	YES-1548-3E + SO 12/4	15	51195	480	36	3	45°F	Cord	62	25,25,38
<b>USTOT-009</b>	YES-3048-3A	30	102390	480	18	3	90°F	-	72	25,25,40
<b>USTOT-010</b>	YES-3048-3A + SO 6/4	30	102390	480	18	3	90°F	Cord	74	25,25,40

**Dimensions (in) of Portable Electric Salamander YES Series**

Series	Length A	Width B	Height C
USTOT-001, 002 & 005 to 008	38	25	25
USTOT-003, 004 & 009 & 010	40	25	25

